

ISO/TC 131/SC 6

Secretariat: BSI

Voting begins on:
2017-04-27

Voting terminates on:
2017-06-22

Hydraulic fluid power — Fluids — Method for coding the level of contamination by solid particles

*Transmissions hydrauliques — Fluides — Méthode de codification du
niveau de pollution particulaire solide*

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/FDIS 4406:2017(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Code definition	1
3.1 General.....	1
3.2 Basis of code.....	2
3.3 Allocation of scale numbers.....	2
3.4 Determination of code using automatic particle counter analysis.....	3
3.5 Determination of code using microscope sizing.....	4
4 Identification statement (reference to this document).....	4
Annex A (normative) Graphical presentation of the code number	5

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. International Standards are drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 6, *Contamination control*.

This third edition cancels and replaces the second edition (ISO 4406:1999), which has been technically revised.

The main changes compared to the previous edition are as follows:

- All year references for ISO 11171 have been removed to ensure that only the most recent version of ISO 11171 is used. This is needed to ensure consistency in the usage and definition of the $\mu\text{m(c)}$ particle sizes used in this document.
- All year references for ISO 4407 and ISO 11500 have been removed to ensure that only the most recent version of these standards are used.

Introduction

In hydraulic fluid power systems, power is transmitted, and controlled, through a liquid under pressure within an enclosed circuit. Solid particle contaminant is always present in the hydraulic fluid and the amount needs to be determined because the contaminant may cause serious problems.

Hydraulic fluid power — Fluids — Method for coding the level of contamination by solid particles

1 Scope

This document specifies the code to be used in defining the quantity of solid particles in the fluid used in a given hydraulic fluid power system.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4407, *Hydraulic fluid power — Fluid contamination — Determination of particulate contamination by the counting method using an optical microscope*

ISO 11171, *Hydraulic fluid power — Calibration of automatic particle counters for liquids*

ISO 11500, *Hydraulic fluid power — Determination of the particulate contamination level of a liquid sample by automatic particle counting using the light-extinction principle*

3 Code definition

3.1 General

The purpose of this code is to simplify the reporting of particle count data by converting the numbers of particles into broad classes or codes, where an increase in one code is generally a doubling of the contamination level.

The original code, in accordance with the first edition of this document, stated the reporting at two sizes $\geq 5 \mu\text{m}$ and $\geq 15 \mu\text{m}$. The sizes in this document account for the use of a different calibration standard for optical automatic particle counters (APCs). The reported sizes are $\geq 4 \mu\text{m(c)}$, $\geq 6 \mu\text{m(c)}$ and $\geq 14 \mu\text{m(c)}$, the last two of these being equivalent to the $5 \mu\text{m}$ and $15 \mu\text{m}$ particle sizes obtained using the ISO 11171 method of calibrating APCs. Throughout this document the use of $\mu\text{m(c)}$ means that particle size measurements are carried out using an automatic particle counter that has been calibrated in accordance with ISO 11171.

Measurement of particles using an optical microscope as specified in ISO 4407 establishes the size of a particle as being equal to its longest dimension, whereas an automatic particle counter derives the size of an equivalent particle from its cross-sectional area, a value different in most cases from that determined using a microscope. The particle sizes to be reported for measurement by microscope $\geq 5 \mu\text{m}$ and $\geq 15 \mu\text{m}$ are unchanged from those specified in the first edition of this document.

CAUTION — Particle counts are affected by a variety of factors. These factors include procurement of sample, particle counting accuracy and the sample container (where used), and its cleanliness. Proper care should be taken during sample procurement to ensure that the sample obtained is representative of the fluid circulation in the system.

3.2 Basis of code

The code for contamination levels using automatic particle counters comprises three scale numbers that permit the differentiation of the dimension and the distribution of the particles as follows:

- the first scale number represents the number of particles equal to or larger than 4 µm(c) per millilitre of fluid;
- the second scale number represents the number of particles equal to or larger than 6 µm(c) per millilitre of fluid;
- the third scale number represents the number of particles equal to or larger than 14 µm(c) per millilitre of fluid.

The code for microscope counting comprises two scale numbers using 5 µm and 15 µm.

3.3 Allocation of scale numbers

3.3.1 The scale numbers are allocated according to the number of particles counted per millilitre of the fluid sample (see [Table 1](#)).

3.3.2 A step ratio of generally two, as given between the upper and lower limits for the number of particles per millilitre in [Table 1](#), has been adopted to keep the number of scale numbers within a reasonable limit and to ensure that each step is meaningful.

Table 1 — Allocation of scale numbers

Number of particles per millilitre		Scale number
More than	Up to and including	
2 500 000		> 28
1 300 000	2 500 000	28
640 000	1 300 000	27
320 000	640 000	26
160 000	320 000	25
80 000	160 000	24
40 000	80 000	23
20 000	40 000	22
10 000	20 000	21
5 000	10 000	20
2 500	5 000	19
1 300	2 500	18
640	1 300	17
320	640	16
160	320	15
80	160	14
40	80	13
20	40	12
10	20	11
5	10	10
2,5	5	9

NOTE: Reproducibility below scale number 8 is affected by the actual number of particles counted in the fluid sample. Raw counts should be more than 20 particles. If this is not possible, refer to [3.4.7](#).

Table 1 (continued)

Number of particles per millilitre		Scale number
More than	Up to and including	
1,3	2,5	8
0,64	1,3	7
0,32	0,64	6
0,16	0,32	5
0,08	0,16	4
0,04	0,08	3
0,02	0,04	2
0,01	0,02	1
0,00	0,01	0

NOTE: Reproducibility below scale number 8 is affected by the actual number of particles counted in the fluid sample. Raw counts should be more than 20 particles. If this is not possible, refer to 3.4.7.

3.4 Determination of code using automatic particle counter analysis

3.4.1 Counting shall be undertaken in accordance with ISO 11500 or another recognized method, using an APC calibrated to ISO 11171.

3.4.2 A scale number shall be allocated to the number of particles equal to or larger than 4 µm(c).

3.4.3 A second scale number shall be allocated to the number of particles equal to or larger than 6 µm(c).

3.4.4 A third scale number shall be allocated to the number of particles equal to or larger than 14 µm(c).

3.4.5 The three numbers shall be written one after the other and separated by oblique strokes (slashes).

EXAMPLE A code of 22/18/13 signifies that there are more than 20 000 and up to and including 40 000 particles equal to or larger than 4 µm(c), more than 1 300 and up to and including 2 500 particles equal to or larger than 6 µm(c) and more than 40 and up to and including 80 particles equal to or larger than 14 µm(c) in 1 ml of a given fluid sample.

3.4.6 When applicable, include either “*” (too numerous to count) or “—” (no requirement to count) notation when reporting the scale number.

EXAMPLE 1 */19/14 means that this sample has too many particles equal to or larger than 4 µm(c) to count.

EXAMPLE 2 —/19/14 means that there was no requirement to count particles equal to or larger than 4 µm(c).

3.4.7 When the raw data in one of the size ranges results in a particle count of fewer than 20 particles, the scale number for that size range shall be labelled with the symbol ≥.

EXAMPLE A code of 14/12/≥7 signifies that there are more than 80 and up to and including 160 particles equal to or larger than 4 µm(c) per millilitre and more than 20 and up to and including 40 particles equal to or larger than 6 µm(c) per millilitre. The third part of the code, ≥7, indicates that there are more than 0,64 and up to and including 1,3 particles equal to or larger than 14 µm(c) per millilitre but less than 20 particles were counted which lowers statistical confidence. Because of this lower confidence, the 14 µm(c) part of the code can be higher than 7, indicating a particle count of more than 1,3 particles per millilitre.

3.5 Determination of code using microscope sizing

3.5.1 Counting shall be undertaken in accordance with ISO 4407.

3.5.2 A scale number shall be allocated to the number of particles equal to or larger than 5 µm.

3.5.3 A second scale number shall be allocated to the number of particles equal to or larger than 15 µm.

3.5.4 In order to relate to counts obtained with an automatic particle counter, the code shall be stated in three-part form with the first part given as “—”.

EXAMPLE —/18/13.

4 Identification statement (reference to this document)

Use the following statement in test reports, catalogues and sales literature when electing to comply with this document:

“Solid contaminant code conforms to ISO 4406, *Hydraulic fluid power — Fluids — Method for coding the level of contamination by solid particles.*”

Annex A (normative)

Graphical presentation of the code number


For automatic particle counter analysis, the contaminant code is determined by:

- allocating a first scale number to the total number of particles equal to or larger than 4 $\mu\text{m(c)}$,
- allocating a second scale number to the total number of particles equal to or larger than 6 $\mu\text{m(c)}$,
- allocating a third scale number to the total number of particles equal to or larger than 14 $\mu\text{m(c)}$, and then
- writing these three numbers one after another separated by oblique strokes (slashes). For example, see 22/18/13 in [Figure A.1](#).

For analysis by microscope, use “—” in place of the first scale number, and allocate the second and third numbers based upon the counts at 5 μm and 15 μm , respectively.

Interpolation is acceptable. Extrapolation is not permissible.

Quote scale number at 4 $\mu\text{m(c)}$, 6 $\mu\text{m(c)}$ and 14 $\mu\text{m(c)}$ levels for automatic particle counters, and at 5 μm and 15 μm for microscope counting.



Key

- X particle size, μm(c)
- particle size, μm
- Y number of particles per millilitre larger than indicated size
- a Scale number.

Figure A.1

