INTERNATIONAL STANDARD

ISO 3320

Third edition 2013-12-01

Fluid power systems and components — Cylinder bores and piston rod diameters and area ratios — Metric series

Transmissions et composants hydrauliques et pneumatiques — Alésages des vérins et diamètres des tiges de piston et rapports de surface — Série métrique





COPYRIGHT PROTECTED DOCUMENT

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Licensed to: Husenica (Rockhill), Denise Ms

Downloaded: 2018-10-23

Single user licence only, copying and networking prohibited © ISO 2013 – All rights reserved

Coı	ntents	Page
Fore	eword	iv
Intr	oduction	v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	1
5	Dimensions	2
6	Area ratios	3
7	Identification statement (reference to this International Standard)	3

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 131, Fluid power systems, Subcommittee SC 3, Cylinders.

This third edition of ISO 3320 cancels and replaces the second edition (ISO 3320:1987) and the second edition of ISO 7181:1991, which have been combined and technically revised.

Introduction

In fluid power systems, power is transmitted and controlled through a liquid (for hydraulics) or a gas (for pneumatics) under pressure within an enclosed circuit.

One component of such systems is the fluid power cylinder. This is a device that converts power into linear mechanical force and motion. It consists of a movable element, i.e. a piston and piston rod, operating within a cylindrical bore.

V

Fluid power systems and components — Cylinder bores and piston rod diameters and area ratios — Metric series

Scope

This International Standard establishes a metric series of cylinder bore and piston rod diameters for hydraulic and pneumatic cylinders, and specifies for each pair of diameters a corresponding standard ratio between the useful areas.

This International Standard applies only to the dimensional criteria of products manufactured in conformity with this International Standard; it does not apply to their functional characteristics.

2 **Normative references**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3, Preferred numbers — Series of preferred numbers

ISO 5598, Fluid power systems and components — Vocabulary

ISO 6099, Fluid power systems and components — Cylinders — Identification code for mounting dimensions and mounting types

Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 apply.

Symbols and units

Symbols and units used in this International Standard are shown in Table 1.

Symbol Designation Unit ALa Cylinder bore diameter mm MMa Piston rod diameter mm $A_1 = \frac{\pi}{4} \cdot AL^2$ Area cylinder cap side cm^2 $A_2 = \frac{\pi}{4} \cdot \left(AL^2 - MM^2\right)$ Area cylinder rod side cm^2 Area ratio Letter codes are in accordance with ISO 6099.

Table 1 — Symbols and units

Dimensions 5

- 5.1 The cylinder bore diameter (AL) is shown in Figure 1 and values are specified in Table 2.
- 5.2 The cylinder rod diameter (MM) is shown in Figure 1 and values are specified in Table 3.




Figure 1 — Identification of bore and rod dimensions

Table 2 — Cylinder bore diameters (AL)

Dimensions in millimetres

A.T.	8	10	12	16	20	25	32	40	50	60	63	80	(90)	100
AL	(110)	125	(140)	160	(180)	200	(220)	250	(280)	320	(360)	400	(450)	500

NOTE 1 An extension upwards of the diameter ranges can be made using the series of preferred numbers given in ISO 3 (R10 for diameters up to bore diameter 100 mm and R20 for bore diameters larger than 100 mm).

NOTE 2 Values in parentheses are non-preferred values and should be used for special applications only.

Table 3 — Piston rod diameters (MM)

Dimensions in millimetres

	4	5	6	8	10	12	14	16	18	20	22	25	28	(30)
MM	32	36	40	45	50	56	(60)	63	70	80	90	100	110	(120)
	125	140	160	180	200	220	250	280	320	360	400	450	-	-

NOTE 1 An extension upwards of the diameter ranges can be made using the series of preferred numbers R20 given in ISO 3.

NOTE 2 Values in parentheses are non-preferred values and should be used for special applications only.

6 Area ratios

- **6.1** For each pair of diameters of bore and piston rod, there is a corresponding ratio between the useful areas.
- Ratios approximately equal to one of the following preferred numbers are shown in Table 4: 6.2

$$1,06 - 1,12 - 1,25 - 1,33 - 1,4 - 1,6 - 2 - 2,5 - 5$$

Moreover, for each pair of diameters of bore (AL) and piston rod (MM), Table 4 gives calculated values of A_1 and A_2 and their corresponding effective value ϕ .

Identification statement (reference to this International Standard)

It is recommended to manufacturers who have chosen to conform to this International Standard that the following statement be used in test reports, catalogues, and sales literature:

"Cylinder bores, piston rod diameters and ratios selected in accordance with ISO 3320, Fluid power systems and components — Cylinder bores and piston rod diameters and area ratios — Metric series."

Table 4 — Bore and piston rod area ratios

Diameters in millimetres, areas in square centimetres

																			·		- 1		
ф	AL	25	32	40	50	63	80	(06)	100	(110)	125	(140)	160	(180)	200	(220)	250	(280)	320	(360)	400	(420)	200
×	A_1	4,91	8,04	12,6	19,6	31,2	50,3	63,6	78,5	95,0	123	154	201	254	314	380	491	616	804	1 018	1 257	1 590	1963
	MM	8	10	10	12	16	20	22	25	28	32	36	40	45	20	26	63	70	80	06	100	110	125
1,06	A2	4,41	7,26	11,8	18,5	29,2	47,1	59,8	73,6	6'88	115	144	188	239	295	356	460	577	754	954	1 178	1 495	1 841
	φ	1,11	1,11	1,07	1,06	1,07	1,07	1,06	1,07	1,07	1,07	1,07	1,07	1,07	1,07	1,07	1,07	1,07	1,07	1,07	1,07	1,06	1,07
	MM	10	12	12	16	20	25	28	32	36	40	45	20	26	89	02	80	06	100	110	125	140	160
1,12	A2	4,12	6,91	11,4	17,6	28,0	45,4	57,5	70,5	84,9	110	138	181	230	283	342	441	552	726	923	1134	1436	1 762
_ice	φ	1,19	1,16	1,10	1,11	1,11	1,11	1,11	1,11	1,12	1,11	1,12	1,11	1,11	1,11	1,11	1,11	1,12	1,11	1,10	1,11	1,11	1,11
nse	MM	12	14	18	22	28	36	40	45	20	26	63	70	80	06	100	110	125	140	160	180	200	220
01,25	A2	3,78	6,50	10,0	15,8	25,0	40,1	51,1	62,6	75,4	98,1	123	163	204	251	302	396	493	650	817	1 002	1 276	1 583
: Hu	φ	1,30	1,24	1,25	1,24	1,25	1,25	1,25	1,25	1,26	1,25	1,25	1,24	1,25	1,25	1,26	1,24	1,25	1,24	1,25	1,25	1,25	1,24
ıser	MM	12	16	20	25	30	40	45	20	26	09	70	80	06	100	110	125	140	160	180	200	220	250
nica	A2	3,78	6,03	9,42	14,7	24,1	37,7	47,7	58,9	70,4	94,4	115	151	191	236	285	368	462	603	763	942	1 210	1 473
(Ro	ф	1,30	1,33	1,33	1,33	1,29	1,33	1,33	1,33	1,35	1,30	1,33	1,33	1,33	1,33	1,33	1,33	1,33	1,33	1,33	1,33	1,31	1,33
)ckh	MM	14	18	22	28	36	45	20	26	63	20	80	06	100	110	125	140	160	180	200	220	250	280
ill),	A2	3,37	5,50	8,77	13,5	21,0	34,4	44,0	53,9	63,9	84,2	104	137	176	219	257	337	415	550	704	877	1 100	1348
Der	φ	1,46	1,46	1,43	1,46	1,48	1,46	1,45	1,46	1,49	1,46	1,48	1,46	1,45	1,43	1,48	1,46	1,48	1,46	1,45	1,43	1,45	1,46
nise	MM	16	20	25	32	40	20	26	63	70	80	06	100	110	125	140	160	180	200	220	250	280	320
%1,6	A2	2,90	4,90	2,66	11,6	18,6	30,6	39,0	47,4	56,5	72,5	8,06	123	159	191	226	290	361	490	638	992	975	1 159
	φ	1,69	1,64	1,64	1,69	1,68	1,64	1,63	1,66	1,68	1,69	1,70	1,64	1,60	1,64	1,68	1,69	1,70	1,64	1,60	1,64	1,63	1,69
	MM	18	22	28	36	45	26	63	20	80	06	100	110	125	140	160	180	200	220	250	280	320	360
2	A2	2,36	4,24	6,41	9,5	15,3	25,6	32,4	40,1	44,8	59,1	75,4	106	132	160	179	236	302	424	527	641	982	946
	φ	2,08	1,90	1,96	2,08	2,04	1,96	1,96	1,96	2,12	2,08	2,04	1,90	1,93	1,96	2,12	2,08	2,04	1,90	1,93	1,96	2,02	2,08
	MM	20	25	32	40	20	63	20	80	06	100	110	125	140	160	180	200	220	250	280	320	360	400
2,5	A2	1,77	3,13	4,52	7,1	11,5	19,1	25,1	28,3	31,4	44,2	58,9	78,3	101	113	126	177	236	313	402	452	573	707
	φ	2,78	2,57	2,78	2,8	2,70	2,63	2,53	2,78	3,03	2,78	2,61	2,57	2,53	2,78	3,03	2,78	2,61	2,57	2,53	2,78	2,78	2,78
	MM	22	28	36	45	26	20	80	06	100	110	125	140	160	180	200	220	250	280	320	360	400	450
Ŋ	A2	1,11	1,88	2,39	3,7	6,5	11,8	13,4	14,9	16,5	27,7	31,2	47,1	53,4	26'2	0,99	111	125	188	214	239	334	373
	φ	4,43	4,27	5,26	5,26	4,76	4,27	4,76	5,26	5,76	4,43	4,93	4,27	4,76	5,26	5,76	4,43	4,93	4,27	4,76	5,26	4,76	5,26
NOTE	Value	s in par	Values in parentheses are non-preferred values and should be used for special applications only	s are no	n-pref	erred v	alues a	no shon	ld be us	ed for s	pecial a	pplicati	ons only	٠,									

